



Ballistic Combat Helmet

Ballistic helmet available in different cuts, with and without the rails, equipped with C.P.E. or Wilcox NVG-shroud. Modern retention system with lockable adjustments together with dial system.

* Image for illustration purposes only, actual configuration can vary depending on customer requirements

Technical Specification		
Ballistic Protection	9mm FMJ @ 426m/s $\pm$ 9m/s (5 shots)	NIJ 0106.01 Protocol NIJ 0108.01 IIIa Threat
Fragmentation Protection	Type 2, 17gr, 1.1g FSP > 700 m/s	STANAG 2920
Blunt Trauma Protection	Peak force transmitted < 5kN Cold, Wet, Hot	EN 397
Environmental Performance	-35°C to +55°C	
Construction	Ultra-High Molecular Weight Polyethylene (UHMWPE)	
Profiles Available	Full-cut, Mid-cut, High-cut	
Colours Available	Black, Green, Tan, Blue – other colours available on request	



Physical Characteristics – Sizing and Mass

Edge Profile	Size	Fits Head Circumference (cm)	Coverage (cm2)	Weight (kg)*
High	Small	52 – 56	960	0.98
	Medium	56 – 58	995	1.00
	Large	58 – 61	1050	1.03
	X-large	61 – 63	1150	1.10
	XX-large	63 – 66	1225	1.14
Mid	Small	52 – 56	1040	1.03
	Medium	56 – 58	1105	1.07
	Large	58 – 61	1155	1.10
	X-large	61 – 63	1230	1.15
	XX-large	63 – 66	1315	1.20
Full	Small	52 – 56	1080	1.05
	Medium	56 – 58	1140	1.09
	Large	58 – 61	1255	1.16
	X-large	61 – 63	1355	1.22
	XX-large	63 – 66	1455	1.28

* Weight shown includes shell, pad system, chinstrap